



# THE PIECE THAT COMPLETES YOUR NEEDS.

The Oxlife Independence by O2 Concepts is a portable oxygen concentrator designed with both patients and providers in mind. Boasting both continuous flow up to 3L/min and pulse settings up to 6 (96 mL), the Oxlife Independence gives patients total freedom with 24/7 oxygen on the go while offering providers a one solution approach to maximize profits in today's turbulent reimbursement climate.

- Patent-pending ESA technology enables the Oxlife Independence to have the longest battery life in its class
- Only POC in class that can be used on all settings while plugged in car (DC) mode



- Integrated DC power supply -no external brick
- Custom split battery configuration allows for "hot swapping" of battery. No loss of oxygen when switching battery

- Integrated cart kit design offers lighter overall weight
- Integrated cart with 6" wheels offers "best in class" mobility
- Medicare HCPCS codes E1390/E1392



- Convenient access to preventative maintenance door for fast and easy filter change
- FAA Approved



## **PULSE FLOW SETTINGS**



- Pulse flow settings in .5 increments for better patient titration
- Large intuitive LCD screen eliminates patient confusion

SETTING	DOSAGE (ML)
.5	8
1	16
1.5	24
2	32
2.5	40
3	48
3.5	56
4	64
4.5	72
5	80
5.5	88
6	96

# **PRODUCT SPECIFICATIONS\***

DIVILIASIONS	neight. 20.2 - Width. 10.9 - Depth. 6	
WEIGHT**	Device: 16.7 lbs • Battery: 1.35 lbs/each	
OXYGEN FLOW RATE	Pulse Dose Settings 0.5-6 in 0.5 increments (8mL-96mL) 1-3 LPM in Continuous Mode in 0.5 LPM increments	
BATTERY DURATION	5.75 hours @ 2 pulse at 20 bpm · 2.5 hours @ 2 LPM continuous	
SOUND LEVEL @ 2 PULSE	40 dBA	
BATTERY RECHARGE TIME***	1.5 hours - 1 battery • 2.5 hours - 2 batteries	
OXYGEN CONCENTRATION	95.6% - 87% at Sea Level at all settings	
OXYGEN OUTPUT PRESSURE	5 psig +/- 1 psig (34 +/- 7 kPa)	

AC POWER

DIMENSIONS

Universal Input: 100-240 VAC · 50-60 Hz · 2.0 Amps Output: 24 Volts · 6.3 Amps

Height: 20.2" . Width: 10.9" . Depth: 8"

DC POWER 12 - 15 VDC · 10 Amps

OPERATING TEMPERATURE 50°F (10°C) to 104°F (40°C)

ALTITUDE OPERATING RANGE 0 - 13,123 Feet (0 - 4,000 Meters)

TRANSPORTATION/STORAGE TEMPERATURE -4°F (-20°C) to 140°F (60°C)

TRANSPORTATION/STORAGE HUMIDITY 0 - 95% Non-Condensing

WARRANTY 3 Year Limited • 1 Year on Accessories/Battery

\*O2 CONCEPTS RESERVES THE RIGHT TO CHANGE SPECIFICATIONS OF THIS PRODUCT AT ANYTIME WITHOUT NOTICE

<sup>\*\*</sup>PRODUCTION WEIGHT DOES NOT INCLUDE CART KIT

<sup>\*\*\*</sup>BATTERY RECHARGE TIME WILL INCREASE IF UNIT IS RUNNING WHILE CHARGING

# ORDERING INFORMATION\*

### PART DESCRIPTION

### **PART NUMBER**

	A 70		<b>N/I</b>	
SY	80.2	<b>8</b> 69	v	0

#### **OXLIFE INDEPENDENCE POC SYSTEM**

 The Oxlife Independence POC System includes oxygen concentrator, 2 batteries, pull handle and wheels, AC and DC power supplies, accessory bag and user manual. 800-0001-2

ACCESSORIES	
ACCESSORY CARRY BAG	800-1003
BATTERY - LITHIUM ION RECHARGEABLE	800-1002
BATTERY CHARGER - DESK TOP SINGLE BAY	800-1004
BATTERY CHARGER - MULTIPLE (6 BAY)	800-1005
CART KIT (INCLUDES WHEELS AND PULL HANDLE)	800-1010
INLET AIR FILTER (PACK OF 6)	800-1006
AC POWER CORD/POWER SUPPLY	800-1000
DC POWER CORD	800-1001
PROTECTIVE COVER	800-1009
PULL HANDLE KIT	800-1011
USER MANUAL	800-1008
WHEELS (2)	800-1007

<sup>\*</sup>US FEDERAL LAW RESTRICTS THESE DEVICES TO SALE BY OR ON THE ORDER OF A PHYSICIAN



14001 MCAULEY BLVD, SUITE 170 . OKLAHOMA CITY, OK 73134 T: 877-867-4008 . F: 877 -867-1314 . WWW.O2-CONCEPTS.COM

